

# NTW-1000

## PORTABLE SURVIVAL CRAFT TWO-WAY VHF RADIOTELEPHONE

Type approval with MED, CCS and VR



- Designed to meet GMDSS requirements related with performance standards for survival craft two-way VHF radio telephone apparatus, such as IMO MSC.149 (77) and IEC 61097-12.
- Compact, lightweight and rugged construction.
- Full marine-use VHF channels can be available.



## SPECIFICATIONS

### ● TECHNICAL SPECIFICATION

Frequency Range: 156.300~162.975 MHz  
 Operating Channels: 19 channels (default)  
 Operating Hours:  $\geq 8$  hours (TX10%, RX10%, Standby80%)  
 Output Power: High 3.0W / Low 0.5W

### ● BATTERY REQUIREMENTS (NBT200)

Battery Voltage: DC 7.2V  
 Storage Temp:  $-30^{\circ}\text{C} \sim +70^{\circ}\text{C}$   
 Shelf Time: max 1 year  
 Expiry Time: 4 years since on board

### ● DIMENSION & WEIGHT

Dimension: 256 (H)  $\times$  51.4 (W)  $\times$  46.2 (D) mm  
 Weight: 400g (Transceiver+Emergency Battery)

## EQUIPMENT LIST

### ● STANDARD

- Transceiver & Antenna 1 set
- Emergency Battery (NBT200) 1 pc
- Belt Clip 1 pc
- Wrist Rope 1 pc

### ● OPTIONS

- Rechargeable Battery (NBT200C) 1 pc
- Charger 1 pc
- AC/DC Adaptor 1 pc



Battery  
Emergency / Rechargeable



Wrist Rope



Bwlt Clip



Battery Charger



AC/DC Adaptor

## SIZE DIMENSION

